

MC403

4G Quad Channel Al Dash Cam

MC403 is an advanced dash camera with 1 built-in camera and 3 remote cameras supporting Al processor to detect driving events such as lane departure, forward collision, headway monitoring warning and improper driver behavior such as using mobile phones, fatigue driving detection, lens covered detectionsmoking detection, lens covered detection to assist drivers in reducing traffic accidents and enhance fleet management efficiency.



Key Features



4-CH Recording with DMS and ADAS

Device supports 1 built-in ADAS dash camera, 1 remote DMS camera and 2 remote cameras, capturing crystal-clear views for double protection and safer daily driving.



Expanded storage

1 TF card for video storage, Max. 512GB



Reliable Witness for Accident

Device detects dangerous driving, captures photos, videos, and GPS position, uploads to cloud for evidence review.



Easy to use

Provide mobile APP, PC, and software platform for video preview and parameter configuration.



Remote Video&Audio Surveillance

Device offers crystal-clear 1080P video and TTS Voice broadcast with microphone & speaker, allowing remote car monitoring anytime, anywhere.



4-CH IP

Support simultaneous data upload to a maximum of 4 IP.



Extension Interface

2 RS232 interface to connect sensors such as fuel sensor, temperature sensor, RFID reader, 2 digital input and 1 digital output.



Panic button

Efficient SOS button and platform swiftly summon rescue services with a single click.



Product specifications

Hardware	Operation system	Linux
	CPU	ARM Dual-Core processor@1.5GHz
	Memory	DDR 512Mb+ Flash 2Gb+TF card (512G)
	GNSS	GPS+BDS(with external G-mouse)
	G-sensor	3-axis acceleration sensor
	Speaker	\checkmark
	Mic	\checkmark
	Sim card	Standard sim
	USB	\checkmark
	LED	Red(Power), Green(Internet&video recording)
	I/O ports	2 digital input,1 digital output, 1 RS232
Camera	Front	1080P ADAS
(support 2–CH AI)	External 1	Cabin view camera 720P
	External 2	Rear view camera 720P
	External 3	Side View camera 720P
	Video encoding	H.264/H.265, default H.264
	Video standards	PAL , NTSC
	Video resolution	Total 1080P at 100 fps
	Compression format	G.711A
Network	4G LTE	
	MC403-EU	FDD LTE: B1/B3/B5/B7/B8/B19/B20
		TDD LTE: B38/B39/B40/B41 (100M)
		WCDMA: B1/B2/B5/B8
		GSM: 850/900/1800/1900MHz
	MC403-American	FDD LTE: B2/B3/B4/B5/B7/B12/B18
		TDD LTD: B38/B41(100M)
		WCDMA: B2/B4/B5
		GSM:850/1800/1900MHz
	WiFi	2.4GHz, 802.11 b/g/n
	Protocol	JT/T808-2011, JT/T808-2019
		JT/T1076-2016, JT/T1078-2016
Others	Power supply	DC: +9V ~ +36V
	Operation Temperature	-20°C to +70°C
	Operation Humidity	20% to 80%
	Net weight	300g
	Dimension	120mm*77mm*55mm
	Certification	CE/FCC